# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** V-TAC

**Supplier's address:** V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

**Model identifier:** 2120434

**Type of light source:**

| | | | |
|---|---|---|---|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | L/N/G Connection | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |


**Product parameters**

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 100 | Energy efficiency class | D |
| Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 11 480 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode power ($P_{on}$), expressed in W | 100,0 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | 0,30 |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 70 |
| Outer dimensions without separate control gear, lighting control — Height | 567 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| Width | 179 | | |
| Depth | 99 | | |

| | | | |
|---|---|---|---|
| parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power[(a)] | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,378<br>0,371 |
| **Parameters for directional light sources:** | | | |
| Peak luminous intensity (cd) | 7 900 | Beam angle in degrees, or the range of beam angles that can be set | 115 |
| **Parameters for LED and OLED light sources:** | | | |
| R9 colour rendering index value | 3 | Survival factor | 1,00 |
| the lumen maintenance factor | 0,96 | | |
| **Parameters for LED and OLED mains light sources:** | | | |
| displacement factor (cos ϕ1) | 0,90 | Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -[(b)] | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 1,0 |

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;


1.0
光谱三原色色比
R=33.1%,G=47.9%,B=19.0%,
0.5
380
460
540
620
700
780

Model placed on the Union market from 06/05/2023.

**EPREL registration number:** 1571919

https://eprel.ec.europa.eu/qr/1571919

**Supplier:** V-TAC Europe Ltd (Importer)

**Website:** www.v-tac.eu

**Customer care service:**

**Name:** V-TAC Europe Ltd.

**Website:** www.v-tac.eu

**Email:** office@v-tac.eu

**Phone:** +359290566

**Address:**
bul. Rozhen 41
Sofia
Bulgaria